

12 Schienenstrahler

SHOPLINE



LUMINAIRE
track light
aluminium
powder-coated white, black
IP20


LED
3000K, 4000K
CRI>80
3-Step MacAdam
ON-OFF

LED LIFETIME (est.)
50.000h L80

OPTICS
square lens optic 85°

DE Schlanker Leuchtenkörper aus Aluminiumstrangpressprofil und pulverbeschichteter Oberfläche. Geeignet zur werkzeuglosen Montage in 3P Stromschienen. Spezielle Reflektoreinheit aus eloxiertem Reinaluminium für homogene vertikale Beleuchtungsstärken und höchste Entblendung. Entwickelt für die Anforderungen in Verkauf- und Präsentationsräumen mit energieeffizienten LEDs und hoher Farbwiedergabe.

EN Streamlined luminaire unit made from extruded aluminium section with a powder coated surface. Suitable for tool-less installation in 3P power rails. Special reflector unit made from anodised pure aluminium provides homogenous vertical illumination and maximum glare suppression. Developed to meet the demands of sales and presentation rooms, with energy-efficient LEDs and high-quality colour reproduction.




Track lights 12

SHOPLINE

ORDER CODE	SYSTEM POWER	LUMINOUS FLUX	COLOUR TEMP.	WEIGHT
SLSL030.12X2X	30W	3.000lm	3000K / 4000K	1,5kg
SLSL055.12X2X	55W	5.700lm		

• - - | X | X | 3 colour temp. | 5 material colour
3 3000K 2 WHITE
4 4000K 3 BLACK

Lichtkurven | Lightcurves



wide 85°

Technische Skizzen | Technical sketches

