02 Floodlights

ATUR2 PRO

Quickinfo

LUMINAIRE

ceiling, wall, mast surface mounted aluminium, grey RAL9006 IP66, IK08





3000K, 4000K, 5700K CRI>70 initial MacAdam 4 SDCM 65.000h L80

OPTIC

symmetric 12° / 15° / 25° / 50° asymmetric 20°x40° / 22°x50° / 30°x108°

ELECTRIC

ON-OFF switchable, 0-10V dim DALI dim

















High performance floodlight optimised for the illumination of sports facilities and large outdoor areas. Manufactured from die-cast aluminium to the highest industry standard. Extremely robust and resistant housing for the toughest environmental conditions. Separate external ballast unit, suitable for pole or direct mounting. Highly efficient and long-life LEDs with uniform light distribution and high luminous flux packages. Stable swivelling mounting bracket suitable for suspended and vertical mounting. Easy handling thanks to well thought-out mounting options.



Types


PRODUCT CODE	POWER	LUMINOUS FLUX	COLOUR TEMP.	WEIGHT luminaire	WEIGHT control unit box
FLAP0750.XXX14.S	750W	103.200lm	3000K 4000K 5700K	13kg	11,2kg
FLAP1250.XXX14.M	1250W	180.900lm		25kg	11,5kg
FLAP1500.XXX14.M	1500W	205.200lm		25kg	14,7kg
FLAP1800.XXX14.L	1800W	241.400lm		33kg	17,6kg








V .. asymmetric 20°x40° Y... asymmetric 22°x50° Z... asymmetric 30°x108° 3 Colour Temp. 3...3000K 4...4000K 5... 5700K


Optic
















Dimension







750W









Pre-assembled ready for connection, suitable for pole or luminaire mounting



Accessories

PRODUCT CODE	DESCRIPTION
FLAPZB010	Laser for precise luminaire adjustment
FLAPZB020	Mounting bracket made of stainless steel

27 26